




# Steatite connection blocks 250V range



Protected against accidental electric contact, brass terminals, nickel plated steel screws.



## 4 mm<sup>2</sup>

<p><b>BA041</b></p>	<p>6 gr.</p>	<p><b>SOLID CONDUCTOR</b> 4mm<sup>2</sup> / 2.5mm<sup>2</sup> / 1.5mm<sup>2</sup> AWG 12 / AWG14 / AWG16</p> <p><b>STRANDED CONDUCTOR</b> 4mm<sup>2</sup> / 2.5mm<sup>2</sup> / 1.5mm<sup>2</sup> AWG 12 / AWG14 / AWG16</p> <p>0.4 N.m      M2.6</p>	<p><b>BA042</b></p> <p>11 gr.</p>
<p><b>BA043</b></p> <p>17 gr.</p>	<p>17 gr.</p>	<p><b>SOLID CONDUCTOR</b> 4mm<sup>2</sup> / 2.5mm<sup>2</sup> / 1.5mm<sup>2</sup> AWG 12 / AWG14 / AWG16</p> <p><b>STRANDED CONDUCTOR</b> 4mm<sup>2</sup> / 2.5mm<sup>2</sup> / 1.5mm<sup>2</sup> AWG 12 / AWG14 / AWG16</p> <p>0.4 N.m      M2.6</p>	<p><b>BA044</b></p> <p>23 gr.</p>

Because of permanent improvement of our products, drawings, descriptions, features used on these data sheets are for guidance only and can be modified without prior advice



Page (.pdf)



Drawing 2D (.dwg)



Drawing 3D (.stp)